

A.D. / O.D. in mm	Wandstärke / Wall Thickness in mm																	
	1,0	1,2	1,5	1,8	2,0	2,5	3,0	4,0	4,8	5,0	5,6	6,0	6,3	7,1	8,0	8,8	10,0	12,0
101,6			3,703		4,913	6,110	7,295	9,628		11,91		14,15						
104			3,792		5,031	6,258	7,472	9,865		12,21		14,50						
108			3,940		5,228	6,504	7,768	10,26	12,22	12,70	14,14	15,09	15,80	17,67	19,73	21,53		
114,3			4,173		5,539	6,893	8,234	10,88	12,96	13,48	15,01	16,03	16,78	18,77	20,97	22,90	25,72	
129			4,717		6,264	7,799	9,322	12,33		15,29		18,20						
133							9,618	12,73	15,18	15,78	17,59	18,79	19,69	22,04	24,66			
139,7			5,112		6,792	8,459	10,11	13,39	15,97	16,61	18,52	19,78	20,73	23,22	25,98			
154			5,641		7,497	9,341	11,17	14,80		18,37		21,90						
159							11,54	15,29	18,25	18,99	21,19	22,64	23,72	26,60	29,79	32,60	36,75	
165									18,96	19,73	22,01	23,53	24,66	27,65	30,97	33,90	38,23	
168,3			6,170		8,202	10,22	12,23	16,21	19,35	20,14	22,47	24,02	25,17	28,23	31,63	34,61	39,04	
177,8									20,48	21,31	23,78	25,42	26,65	29,89	33,50	36,68	41,38	
194									22,40	23,31	26,02	27,82	29,16	32,73	36,70	40,19	45,38	
219,1									25,37	26,40	29,49	31,53	33,06	37,12	41,65	45,64	51,57	61,29
244,5									28,37	29,53	32,99	35,29	37,01	41,57	46,66	51,15	57,83	68,81
273,1									31,76	33,06	36,94	39,52	41,45	46,58	52,30	57,36	64,88	77,27
323,9									37,77	39,32	43,96	47,04	49,34	55,47	62,32	68,38	77,41	
355,6									41,53	43,23	48,34	51,73	54,27	61,02	68,58	75,26	85,23	

andere Abmessungen auf Anfrage

other dimensions on request

Qualitäten / qualities:

 EN 10217-1
 EN 10219
 EN 10305-3

 DIN 1615
 DIN 1626
 DIN 2394
 DIN 2458

API 5L

ASTM A53

Güten / grades:

 P235TR1 / P235TR2
 S235JRH / S275J0H / S275J2H / S355J0H / S355J2H
 E235

 St 33
 St 37.0 / St 44.0 / St 52.0

B / X42 / X46 / X52

A / B